

evo²



CONSTANT EXTRACTION Separated steam boiler and brewing group with our patented multi boiler technology. Set temperature with 0,1 degree precision and find your sweet spot.

USABILITY 54 mm-diameter portafilter, ergonomic handgrips, easy and quick milk frothing. Possibility to use the machine with dc system modules (GCS, MCS, OCS).

ENERGY SAVING Independent group give the possibility to turn off unused brewing groups or the boiler. All the material of evo2 guarantee the perfect thermal stability.

SUSTAINABILITY Lead Free: all parts exposed to water are in lead-free alloy (CW510L), certified by NSF. Construction materials are totally recyclable.

BLACKBOARD EDITION Make it your own. Customize your machine and add a personal touch on it. Let's play, write, erase and keep on creating.



2 GROUPS

| | |
|----------------------------------|--------------------|
| dimensions (w x h x d) | 730 x 510 x 525 mm |
| weight | 67 kg |
| power consumption (24h-stand-by) | 7,9 kW |
| max power | 4,3 kW |
| connected load | 220/400 V 3 N |
| boiler capacity | 7,5 l |
| capacity of group heads | 0,5 l |

**DALLA
CORTE**
*Make it
Better*



ARCTIC WHITE

2 groups

1-MC-EVODUE-2-W-400



SPARKLING RED

2 groups

1-MC-EVODUE-2-R-400



NEBULA BLACK

2 groups

1-MC-EVODUE-2-N-400



QUARTZ GREY

2 groups

1-MC-EVODUE-2-Q-400



BLACKBOARD

2 groups

1-MC-EVODUE-2-C-400

GCS Grinder Control System - connection with dc one or dc two grinder
MCS Milk Control System - requires a specific steam wand
OCS Online Control system - remote control with LAN module and connection cable